

電阻隔離雙輸出傳送器

(DUAL OUTPUT RESISTANCE ISOLATED TRANSMITTER)

MODEL
DTR



特點(FEATURES)

- 精確度0.1%滿刻度 (Accuracy 0.1%F.S.)
- 多種輸入與輸出選擇(Wide selection of input/output range)
- 輸入與輸出絕緣耐壓2千伏特/1分鐘(Dielectric strength 2KVac/1 min. (input/output/power))
- 寬範圍交直流兩用電源設計(Wide input range for auxiliary power)
- 尺寸小,穩定性高(Dimension small and High stability)


1.MODEL:DTR- (選購型號)

NO	Input Range	NO	Input Range	NO	Output 1 Range	NO	Output 2 Range	NO	Aux. Power
1	0-100 ohm(10mA)	6	0-10K ohm(100uA)	C	DC1-5V	C	DC1-5V	A	AC/DC 18-60V
2	0-500 ohm(2mA)	7	0-100K ohm(10uA)	D	DC0-10V	D	DC0-10V	B	AC/DC 90-260V
3	0-1K ohm(1mA)	9	SPECIFIED	F	DC0-1mA	F	DC0-1mA		Less 4VA for AC/DC input
4	0-2K ohm(500uA)		() for sensing current	I	DC4-20mA	I	DC4-20mA		
5	0-5K ohm(200uA)			R	SPECIFIED	R	SPECIFIED		


2.SPECIFICATION (主要規格)

- Measuring accuracy (精確度) : 0.1% F.S. (23 ± 5)
- Response time (輸出反應速度) : < 250 ms (0-90%)
- Output drive capability (輸出負載能力) : < 10mA for voltage mode
< 10V for current mode
- Output ripple (p-p) (輸出之漣波) : < 0.1% F.S.
- Zero (offset) range (歸零調整範圍) : 0- ± 5% F.S.
- Span (scale) range (最大值調整範圍) : 0- ± 10% F.S.
- Temp. coefficient (溫度係數) : 100ppm/ (0-50)
- Isolation (隔離特性) : Input/Output 1/Output 2/Power/Case
- Insulation Resistance (絕緣阻抗) : >100M ohm with 500V DC
- Dielectric strength (絕緣耐壓能力) : 2KVac/1 min. (input/output 1/output 2/power)
1600Vdc (input/output 1/output 2)
- Operating condition (使用環境條件) : 0-50 (20 to 90% RH non-condensed)
- Storage condition (存放環境條件) : 0-70 (20 to 90% RH non-condensed)
- Construction (安裝方式) : Socket/plugin type with barrier terminals

3.Terminal conection(接線圖)



4.Dimension(unit:mm)(外型尺寸)



鉅斧科技股份有限公司

AXE TECHNOLOGY CO., LTD.
電話: (02) 2276-3475
傳真: (02) 2276-3479

