

微電腦型脈波輸入瞬間量, 累積量顯示控制電錶

(MICROPROCESS RATE & TOTALIZER CONTROLLER METER)(PULSE INPUT)

MODEL
MFRT



特點(FEATURES)

- 顯示範圍0至19999(瞬間量), 0至999999999(累積量)可任意規劃
(Programmable rate 0 to 19999 digit (rate), 0 to 999999999 digit (totalizer))
- 精確度0.03%滿刻度(瞬間量) (Accuracy 0.03% F.S. (rate))
- 頻率輸入範圍 0.01Hz 至 10KHz (Input range form 0.01Hz to 10KHz)
- 瞬間量與累積量時間基數可任意規劃(1 或 60 或 3600 秒)(Programable time base(1,60,3600 second))
- 瞬間量之最高顯示值可任意規劃(0至19999)(Programable rate 0 to 19999 digit)
- 時間基數內之總輸入脈波數可任意規劃(0至999999999)
(Programmable totalizer of pulse in time base (0 to 999999999 digit))
- 累積量之輸入脈波比例刻劃調整可任意規劃(0.00001至9999.99999)
(Programmable scale factor (0.00001 to 9999.99999)(totalizer))
- 具有二組警報功能(Dual alarm function) (Optional)
- 15 BIT 隔離類比輸出(15 bit DAC isolating analog output function) (Optional)
- 數位 RS-485 界面(Digit RS-485 interface function) (Optional)

1.MODEL:MFRT- (選購型號)

NO	Input Type	NO	Input Type	NO	Input Type	NO	Input rates	NO	Alarm	NO	Analog output	NO	RS-485 output	NO	Aux. Power
A	Pulse(I/L)(5V)	D	Magnetic pick-up (AC50mV-1.5V)	F	AC2-60V	1	50 pulse/sec	0	Non-alarm	N	None	N	None	A	AC/DC 18V-60V
B	Pulse(NPN)(12V)			O	SPECIFIED	2	5000 pulse/sec	1	One-alarm	I	DC4-20mA	Y	RS-485	B	AC/DC 90V-260V
C	Pulse(PNP)(12V)	E	Magnetic pick-up (AC500mV-15V)				50 pulse/sec. for relay contacts input	2	Two-alarm	V	DC0-10V		Modbus RTU mode		Less 5VA for AC/DC input
									R	SPECIFIED					

2.SPECIFICATION (主要規格)

- Measuring accuracy : 0.03% F.S.(rate) (23 ± 5)
(精確度)
- Count input type : Switch selectable current sourcing(NPN)
(脈波輸入型式)
or current sinking (PNP)
- Count input trigger levels : HI bias (CMOS) (V_{IH}=7.5V, V_{IL}=5.5V)
(脈波動作電位)
Lo bias (TTL) (V_{IH}=3.7V, V_{IL}=2.0V)
- Max. count rates : <10KHz (50% duty cycle)(pulse)
(最高輸入頻率)
<10KHz (magnetic pick-up)
- Sampling time : 10 cycles/sec. (>10Hz)(rate)
(取樣時間)
f cycle/sec. (<10Hz)(rate)
- Readout (compare) range : 0-19999 adjustable(rate)
(顯示值(比較值)範圍)
0-999999999 adjustable (totalizer)
- Alarm action : Hi or Lo adjustable
(繼電器動作方向)
- Relay contact output : AC 250V-3A, DC 30V-5A
(繼電器容量)
- Analog output resolution : 15 bit DAC (isolating)
(類比輸出解析度)
- Response time : < 1/f + 10ms (0-90%)
(反應速度)
- Output drive capability : <10mA for voltage mode
(輸出負載能力)
<10V for current mode
- Output ripple (p-p) : <0.1% F.S.
(輸出之漣波)
- RS-485 baud rate : 19200/9600/4800/2400 selective
(傳輸速率)
- RS-485 adress : "01"- "FF"
(通訊位址)
- RS-485 protocol : Modbus RTU mode
(通訊協議)
- Display : Red high efficiency LEDs high 10.16 mm (0.4")
(顯示幕)
- Parameter setting : Touch switches
(參數設定方式)
- Memory mode : Non-volatile E² PROM memory
(記憶方式)
- Dielectric strength : 2KVac/1 min. (input/output/power)
(絕緣耐壓能力)
1600 Vdc(input/output)
- Operating condition : 0-50 (20 to 90% RH non-condensed)
(使用環境條件)
- Storage condition : 0-70 (20 to 90% RH non-condensed)
(存放環境條件)

3.OUTSIDE DIMENSION AND CONNECTION DIAGRAM

(外型尺寸與開孔尺寸與配線圖)

