

Oseco's Transportation Disks Move You on the Right Track









Transportation Disks

HALMA GROUP COMPANY OSECO HP-RC, HCl-RC, ICD & CRC

TRANSPORTATION DISKS



Hygienic Disks

Panels







Oseco's reliability and precision make the Oseco difference.

Oseco Transportation Disks conform to ICC regulations in providing reliable overpressure protection of railroad tank cars and other specific containers transportable by truck or ship. Our skilled craftsmen oversee the complete manufacturing process and our thorough testing assures a consistent burst pressure and higher accuracy.

Specifications for Oseco's transportation disks:

HP-RC

The economical HP-RC is constructed of durable Ryton plastic. Ryton gives excellent corrosion resistance and resists premature bursting during humping caused during coupling of railcars. The HP-RC fits the standard threaded or bolted railroad tank car safety vent. Optional Teflon® liners are available on either or both sides of the disk.

HCI-RC

The HCI-RC has a large 4.75" OD typically used in rubber lined tank car. Made with durable Ryton plastic, the HCI-RC comes as standard with Teflon® liners and gaskets adhered to both sides, giving maximum corrosion resistance.

CRC

A metal disk with a 3.125" outside diameter, the Composite Rail Car (CRC) fits the standard threaded or bolted railroad tank car safety vent. Should vacuum occur during unloading or while the car is in transit, the stainless steel vacuum support protects the seal.

ICD

The ICD is a high-performance scored disk used to protect intermodal containers. The ICD utilizes a nickel disk, stainless steel centering ring, as well as a Teflon® liner on the process side and Teflon gaskets.



Made in the USA Since 1981



OSECO

1701 West Tacoma, **Broken Arrow, Okla.** 74012, U.S.A. voice 1.918.258.5626 • fax 1.918.251.7662

EUROPE: OSECO EUROPE BV

Box 23, 8330AA Steenwÿk, the Netherlands voice 31.521.522.578 • fax 31.521.510.405

ASIA: HALMA ASIA OSECO DIVISION

Pantech Complex, Block 192 Pandan Loop #501, Singapore 128381

voice 65.745.2936 • fax 65.745.0467

www.oseco.com • 1.800.395.disk • info@oseco.com

GROUP

COMPANY

